Before Starting Work.

·7

NHOW ENTINATS EROHER

SIIIIAMHAU **CEMENT MIXES AND CONTACT**

- cause contact dermatitis. Wet cement mix is a substance that can 1
- the substance is in contact with the skin. when the skin reacts to certain substances. The rash can vary but it is usually itchy and causes flaky skin and only occurs where the cutoframe is in control with the skin Contact dermatitis is a rash that may occur
- Wash cement or plaster mixes from skin immediately. Thoroughly rinse out eyes and seek medical advice immediately. 3
- Mild dermatitis will heal providing there is no further contact. If the rash persists seek medical advice. Learn more about contact dermatitis visit www.bcds.org.uk
- be worn to prevent the mixes coming into contact with bare skin Gloves, long sleeves and full trousers must ·9

WORK AREA

- Do not use this machine where there is a danger of explosion. It will ignite tumes from petrol, or gas cylinders. -1
- εαιε αυα τυαι μο-ομε ις close by αυα coni Make sure that the work area is clear and
- Protect other people from the noise and wet cement. Warn others to keep away, set up an exclusion zone around the area where the poker vibrator is being used with physical barniers, barnier tape and signs. Keep ohildren and animals away when using this equipment 3 ractions
- Work should stop immediately assisting anyone, other than those directly assisting 16 .insmitting this equipment.
- unppie' unppieu e Clear the area of trip hazards such as ·c with the work, enter the exclusion zone.
- Position the drive unit so that you can easily reach all of the concrete you need to work on. Make sure that the flexible drive is not
- going to be damaged by traffic, or create

2450 Regents Court The Crescent Birmingham Business Park Solihull B37 7YE

thoritatively interpret the law

vensue. :lism3

1

·9

·G

31

'Z

1

РОКЕЯ VIBRATOR

.ueudinbe

0114 Poker vibrator - 110/230v

Poker Vibrator

The rules and procedures in force where people are at work may require the person responsible for this equipment to carry out a specific risk assessment.

Cement mixes are harmful to eyes, lungs and skin. Take precautions to prevent contact with

This poker vibrator is designed for use in fresh concrete to remove air voids and speed the

The action of this poker vibrator can cause injury or damage if the machine is not used in

The following items of personal protective equipment must be worn: goggles; dust mask- a

minimum of ffp2 protection; ear muffs or plugs giving protection to reduce exposure to 87dB(A) at the ear; Safety boots; industrial quality gloves; residual-current device (RCD) if

This machine must not be used by young persons, or by anyone under the influence of drugs

This poker vibrator is designed for operation by an able bodied adult. Anyone with either

Some poker vibrators are heavy machines, get help if you have to unload it from your

temporary or permanent disability must seek expert advice before using it.

It is important to read all of this leaflet

BEFORE using the Poker Vibrator

1.

3

4

5.

6

10

12

working safely.

cement mix.

or alcohol

start on the main task

a careful and controlled way

using a 230 volt (mains) supply.

A personal first-aid kit should be available.

vehicle. Do not lift beyond your own capabilities.

Plan your work and think ahead to make sure you will always be

you have not used this type of poker vibrator before,

familiarise yourself with how the machine works before you

Electricity is dangerous and must always be used with great care.

Electricity and water make a very dangerous combination. Keep

use of trapped water. It is not designed for any other purpose

electrical equipment away from rain and water.

www.use.org.uk .euoydəjə

เมฆเติมชุย.org.uk 44 (0) 121 380 4600 44 (0) 121 333 4109

Check the drive unit, flexible drive and couplings, and vibrating head. If anything is found to be damaged, do not use the poker vibrator. Contact the hire company.

Anybody who is working close by will also need to wear identical personal protective

Industrial quality gloves, long sleeves, and full trousers must be worn to prevent the mixes coming into contact with bare skin.

Vibration from using this machine can be hardown by March and the period explored starting work, and wear industrial quality gloves to keep hards warm while working. Find out free the effects of vibration or the file company for a copy of the HAE And erm to find erm of the period of the file converse.

Remember that you may have to stand in

stery boots/wellingtons must be worn

This equipment is likely to cause noise noise to 93 dB(A) - west appropriate ear mutifs or plugs giving hearing protection for the level as a minimum.

Goggles must be worn when working with this machine.

tiapping clothing that could get caught in

The following items of personal protective membrane (PHE) are (PHE) are protective about be worn whenever the poker vibrator is used. Particular jobs or

onments may require a higher level of sction. Ensure there is no loose or

visit www.hse.gov.uk/vibration

muminim as a ninimum.

the machinery.

protection.

SROTARAGO

effort has been made by HAE/EHA to ensure that the information given in this document and supporting n is accurate and not misleading. HAE/EHA cannot accept responsibility for any loss or liability perceived to have arisen from the use of any such document/material. Only Acts of Parliament and Statutory Instruments have the force of law and only the courts can a

44 (0) 121 380 4600 44 (0) 121 333 4109 Email e.ora.uk w.hae.org.uk

ou cable

will be 110v or 230v.

YTERCAL SAFETY

bingging it into the supply.

residual-current device (RCD).

-1

230 volt socket. Do not use any 230v

d, plug the transformer directly into

If a portable transformer requires to be

fitted. 230v machines will have either a normal square pin plug fitted, or a blue industrial plug. Read the instructions below for your machine.

pulg listraubni wolley a yellow industrial plug

The machine will only operate on one voltage: it

before switching the vibrating poker on, locate the stop control. Make sure that the vibrating poker is switched off before

Check on how the on/off switch operates

230v mains will have either a normal square pin plug fitted, or a blue industrial plug, which must be connected through a coniected through a

not to injure yourself when noving it about i timay be heavier than you think. Machines designed of benginer about Saturations and the second second second about the second second second second second about the second sec

Machines with a cylindrical yellow industrial plug fitted are designed to run off an 110v aupply. The hire company will have provided a portable transformer if the machine needs to be powered from a transformer has been supply. If a portable transformer has been supplied, take care transformer has been supplied, take care transformer has been supplied.

Check that the plug on the machine matches the supply. Do not try to force

connections or improvise them.

110 VOLT MACHINES (YELLOW PLUG)

Birmingham Business Park Solihull B37 7YE

siou csple > poker vibrator.

connections are dry and sate.

230v: Wall socket > RCD > any necessary

ssary extension cable > poker vibrator.

Wall socket > transformer >

Make sure that any extension cable

might be trapped, and places where vehicles might run over it. Unroll it fully or it will overheat and could catch fire.

Lay it out carefully avoiding liquids, sharp edges, doorways or windows where it

Plug it directly into the RCD.

hire company. If the hire company has not given any special instructions, a suitably rated heavy duty extension cable must be

It an extension cable is required to be used, follow any special instructions given by the

Use the "TEST" button to check that the Use the "TEST" bare of the Sect Reset. Reset and PRCD is working each time it is used. Reset the Mith if

help to protect against electric shock if the Use a residual current device (RCD) plugged directly in to the 230volt socket. Plug the machine into the C30volt with with the WCD.

avoiding liquids, sharp edges, doorways or windows where it might be trapped, and Unroll it fully or it will overheat and could cather the

Lay the extension cable out carefully

any special instructions, a suitably rated heavy utu, 1100 extransion cable and beind beaviewed, not ionger than 50 metres (160 feet). An extension cable must only be used heween the transformet and the acchine.

company. If the hire company has not given

It an extension cable is required, follow any special instructions given by the hire

cable or machine gets damaged.

ctions are dry and safe d. Make sure that any extension cable

(SOUARE PIN OR BLUE PLUG)

S30 VOLT MACHINES

catch fire.

2450 Regents Court The Crescent

it again.

goes hard.

not leave it lying in dirt.

efficiency.

1. 2.

3.

6.

7.

8.

9.

10.

11.

12.

13.

16.

17.

guì

If the vibrating head does not vibrate when the machine is started, tap the nose onto a hard surface. Do not tap or hit the outer housing of the head.

You may need to allow the unit to warm up for a few minutes in cold weather for maximum

from HAE by Skipton Hire Centre (SHC) Limited, Document expires on

For more information on

health and safety in construction go to

www.hse.gov.uk/construction/

Watch out for signs that vibration may be affecting your hands. If fingers start to tingle or feel 4 numb, take a short break from using the machine. Exercise fingers to encourage blood circulation. Find out more about vibration. Ask the hire company for a copy of the HAE

Using the Poker Vibrator

HSE

Wear protective equipment including gloves, goggles and safety boots

Do not touch the vibrating part of the poker while it is in operation.

Take care not to accidentally pull the plug from the socket.

Stop the unit and unplug it if leaving the machine unattended.

Do not disengage the flexible drive coupling while the motor is running.

damage to the surface and the poker.

- leaflet no. 2150 Hand-arm vibration or visit www.hse.gov.uk/vibration

- To help prevent vibration affecting hands, operate the machine for shorter periods, or share
- 5

Always move and withdraw the vibrating head steadily - this will help avoid creating voids.

Do not lay the vibrating poker on a hard surface while it is still vibrating. It will cause

If the cable is found to be cut or damaged in any way, switch off and unplug at the socket before inspecting it. If the cable attached to the drive unit is damaged, stop using the

machine. Contact the hire company. If an extension cable has been damaged, do not use

If the flexible drive has been disengaged, take care to keep the open end of it clean - do

If the equipment does not work properly do not attempt to repair it. Contact the hire company.

You may want to read this leaflet again. Please keep safely it until you finish work.

Copyright Hire Association Europe April 2000

Any unauthorised reproduction - manually or electronically - is STRICTLY prohibited

:0011

ť

3

3.

.2

.ti dtiw beilqqua

:linumary:

14. The poker vibrator must be cleaned as soon as work is finished before any concrete on it

- Take care not to bend the flexible drive through tight angles, for example over shuttering.
- the job with a workmate. Keep hands warm wearing gloves may help do this.