









PCLX 12/40E ELECTRIC PLATE COMPACTOR





FEATURES & BENEFITS

- High performance 12kN vibration unit for excellent travel speed.
- High Compaction Force reduce operating time.
- Environmentally friendly, 1.5kW zero emission Electric Motor for use indoors & in poorly ventilated areas.
- Low HAV design allows longer, safer usage.
- Efficient Electric Motor is ideal for night time & urban usage.
- Centrifugal Clutch for soft start & reduced current surge.
- Professional 16amp power inlets for effective cable management.
- Front & rear manual handling points for easy 2-man lift.
- Removable, ultra low folding operator's handle for ease of transportation and storage.
- 8mm thick long life base plate for optimum compaction and reliability.
- Engineered to be robust and durable for rental and heavy contractor use.
- No fuel or engine maintenance = higher return on investment.
- Class 1 Earthed Appliance.
- Block Paving Pad option available.



ECO FRIENDLY, ZERO EMISSION ALLOWS INDOOR USAGE



1.5KW ELECTRIC MOTOR & **12KN VIBRATOR**



TECHNICAL SPECIFICATIONS

Model	PCLX 12/4	OE.			5 8
Width	(mm)	380			
Operating Height	(mm)	875			1
Operating Length	(mm)	1050		-	
Storage Height	(mm)	560			1
Storage Length	(mm)	820			
Plate Contact Area (W x L)	(mm)	380 x 364			
Weight	(kg)	50	CABLE S	TORAGE HO	OKS 0
Motor Power	(Hp / kW)	2 / 1.5	THE OP	ERATOR HA	ANDLE
Motor RPM		2800			
Motor Protection		IP44			
Static Pressure	(kg/m^2)	388			
Centrifugal Force	(kN)	12	Model	110V	
Max. Gradient	(°)	20	Full Load Current	(Amp)	14.2
Max. Ext Cable Length	(mtr)	25	Min. Transformer Size	(kVA)	3.3
Travel Speed	(m/min)	24			
Sound Power Level	(dB(A))	104	Model	230V	
3 Axis Vibration	(m/sec^2)	5.6	Full Load Current	(Amp)	6.66
Usage Time	(mins)	95.6	Min. Transformer Size	(kVA)	N/A



ALTRAD BELLE Sheen, Nr. Buxton, Derbyshire, SK17 OEU, GB Tel. +44 (0)1298 84606 - Fax +44 (0)1298 84722 - Email: sales@altrad-belle.com www.Altrad-Belle.com www.ALTRAD-Belle247.com

